ELECTRIC ARC ANTIFLAME

ARC-LR17055

EN 343 3 3

EN ISO 20471 3

EN ISO 11612
A1 B1 C1 D3 E3 F1

EN 1149-5

EN 13034
Type PB [6]

EN ISO 11611
Class 1 A1

IEC 61482-2
Class 2

RIS-3279-TOM
Only col. 05

ATPV
42,4 cal/cm²

Breathable, wind & waterproof

Adjustable cuffs

Adjustable hem

LOXY®
Loxy reflexes

Breathable, wind and waterproof with taped seams

Waterproof: ≥13.000 MM
Breathability: 10.000g/m2/24h

Colours and sizes

05 Hi-Vis Orange	S - 4XL
53 Saturn Yellow	S - 4XL

No to PFAS chemsec

OEKO TEX® STANDARD 100 2176-341 DTI www.oeko-tex.com

GB

Multinorm Hi-Vis Jacket in heavy tear-resistant quality with lining
99% Polyester, 1% Carbon Grid with Kromotex, 270 g/m²
Lining: 85% CV FR, 15% Para-aramid, 165 g/m²
IEC 61482-2-2009, Class 2, ATPV 42, 4 cal/cm²

- Detachable hood with zipper and elastic drawstring
- Hidden zipper with velcro closure
- Two loops for walkie-talkie / gas detector or similar
- Adjustable and elasticated sleeves with velcro
- Drawstring at waist
- Two chest pockets with velcro
- Two chest pockets with zipper
- Two front pockets with velcro

Care instructions

40°

Do not use any softeners
Do not use bleach
Wash with similar colours
Ensure the zipper is fastened
Dry inside out

LYNGSØE RAINWEAR