# ELECTRIC ARC ANTIFLAME

## MULTINORM JACKET IN HEAVY TEAR-RESISTANT QUALITY

**ARC-LR17055**

EN 343 3 3

EN ISO 20471 3

EN ISO 11612
A1 B1 C1 D3 E3 F1

EN 1149-5

EN 13034
Type PB [6]

EN ISO 11611
Class 1 A1

IEC 61482-2
Class 2

RIS-3279-TOM
Only col. 05

ATPV
42,4 cal/cm²

Breathable, wind & waterproof

Adjustable cuffs

Adjustable hem

LOXY®
Loxy reflexes



**Breathable, wind and waterproof with taped seams**

Waterproof: ≥13.000 MM
Breathability: 10.000g/m2/24h

**Colours and sizes**

| | |
|---|---|
| 05 Hi-Vis Orange | S - 4XL |
| 53 Saturn Yellow | S - 4XL |

No to PFAS
chemsec

OEKO TEX® STANDARD 100
2176-341
DTI
www.oeko-tex.com

**GB**

**Multinorm Hi-Vis Jacket in heavy tear-resistant quality with lining**
99% Polyester, 1% Carbon Grid with Kromotex, 270 g/m²
Lining: 85% CV FR, 15% Para-aramid, 165 g/m²
IEC 61482-2-2009, Class 2, ATPV 42, 4 cal/cm²

- Detachable hood with zipper and elastic drawstring
- Hidden zipper with velcro closure
- Two loops for walkie-talkie / gas detector or similar
- Adjustable and elasticated sleeves with velcro
- Drawstring at waist
- Two chest pockets with velcro
- Two chest pockets with zipper
- Two front pockets with velcro

**Care instructions**

40°

Do not use any softeners
Do not use bleach
Wash with similar colours
Ensure the zipper is fastened
Dry inside out

LYNGSØE RAINWEAR